

DCY性能表

网站：www.ks-dcy.com

註：入口流量 Qs=m³/min

機型 Model	轉速 RPM	TypeDCY-40 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-40	1050	1.32	0.52	1.10	1.14	0.79	1.10	0.93	1.06	1.50	0.67	1.32	2.20						
	1150	1.48	0.57	1.10	1.30	0.86	1.50	1.08	1.16	2.20	0.81	1.45	2.20						
	1250	1.63	0.62	1.10	1.45	0.94	1.50	1.24	1.26	2.20	1.00	1.58	2.20						
	1350	1.79	0.67	1.10	1.60	1.01	1.50	1.40	1.36	2.20	1.17	1.70	2.20						
	1450	1.95	0.71	1.10	1.75	1.09	1.50	1.55	1.46	2.20	1.33	1.83	3.00	1.08	2.20	3.00	0.80	2.57	3.00
	1550	2.10	0.76	1.10	1.91	1.16	2.20	1.71	1.56	2.20	1.49	1.95	3.00	1.24	2.35	3.00	0.95	2.75	4.00
	1650	2.26	0.81	1.10	2.06	1.24	2.20	1.86	1.66	2.20	1.64	2.08	3.00	1.39	2.50	3.00	1.11	2.93	4.00
	1750	2.41	0.86	1.50	2.22	1.31	2.20	2.02	1.76	2.20	1.80	2.21	3.00	1.55	2.65	4.00	1.26	3.10	4.00
	1850	2.57	0.91	1.50	2.37	1.39	2.20	2.17	1.86	3.00	1.95	2.33	3.00	1.70	2.81	4.00	1.42	3.28	4.00
	1950	2.72	0.96	1.50	2.53	1.46	2.20	2.33	1.96	3.00	2.11	2.46	3.00	1.86	2.96	4.00	1.57	3.46	4.00

機型 Model	轉速 RPM	Type DCY-50 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-50	1050	2.13	0.75	1.10	1.88	1.20	1.50	1.64	1.65	2.20	1.39	2.10	3.00	1.11	2.55	4.00	0.79	2.99	4.00
	1150	2.40	0.82	1.50	2.15	1.32	2.20	1.91	1.81	3.00	1.66	2.30	3.00	1.38	2.79	4.00	1.06	3.28	4.00
	1250	2.67	0.90	1.50	2.42	1.43	2.20	2.18	1.96	3.00	1.93	2.50	3.00	1.65	3.03	4.00	1.33	3.56	5.50
	1350	2.93	0.97	1.50	2.68	1.54	2.20	2.44	2.12	3.00	2.19	2.70	4.00	1.91	3.27	4.00	1.59	3.85	5.50
	1450	3.20	1.04	1.50	2.95	1.66	2.20	2.71	2.28	3.00	2.46	2.90	4.00	2.18	3.51	5.50	1.86	4.13	5.50
	1550	3.47	1.11	1.50	3.22	1.77	3.00	2.98	2.43	3.00	2.73	3.10	4.00	2.45	3.76	5.50	2.13	4.42	5.50
	1650	3.74	1.18	2.20	3.49	1.89	3.00	3.25	2.59	3.00	3.00	3.30	4.00	2.72	4.00	5.50	2.40	4.70	5.50
	1750	4.01	1.26	2.20	3.76	2.00	3.00	3.52	2.75	4.00	3.27	3.50	5.50	2.99	4.24	5.50	2.67	4.99	7.50
	1850	4.28	1.33	2.20	4.03	2.12	3.00	3.79	2.91	4.00	3.54	3.70	5.50	3.26	4.48	5.50	2.94	5.27	7.50
	1950	4.55	1.40	2.20	4.30	2.23	3.00	4.06	3.06	4.00	3.81	3.89	5.50	3.53	4.73	5.50	3.21	5.56	7.50

機型 Model	轉速 RPM	Type DCY-65 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-65	1050	2.87	0.97	1.50	2.67	1.46	2.20	2.42	2.05	3.00	2.14	2.63	4.00	1.83	3.21	4.00	1.46	3.79	5.50
	1150	3.23	1.06	2.20	3.03	1.60	2.20	2.78	2.24	3.00	2.50	2.88	4.00	2.19	3.52	5.50	1.82	4.15	5.50
	1250	3.59	1.16	2.20	3.39	1.74	2.20	3.14	2.44	3.00	2.86	3.13	4.00	2.55	3.82	5.50	2.18	4.52	5.50
	1350	3.95	1.25	2.20	3.75	1.88	3.00	3.50	2.63	4.00	3.22	3.38	5.50	2.91	4.13	5.50	2.54	4.88	7.50
	1450	4.31	1.34	2.20	4.11	2.02	3.00	3.86	2.83	4.00	3.58	3.63	5.50	3.27	4.43	5.50	2.90	5.24	7.50
	1550	4.67	1.43	2.20	4.47	2.16	3.00	4.22	3.02	4.00	3.94	3.88	5.50	3.63	4.74	5.50	3.26	5.60	7.50
	1650	5.03	1.53	2.20	4.83	2.30	3.00	4.58	3.22	4.00	4.30	4.13	5.50	3.99	5.05	7.50	3.62	5.96	7.50
	1750	5.39	1.62	2.20	5.19	2.44	4.00	4.94	3.41	5.50	4.65	4.38	5.50	4.35	5.35	7.50	3.98	6.32	7.50
	1850	5.75	1.71	2.20	5.55	2.58	4.00	5.30	3.61	5.50	5.02	4.63	7.50	4.71	5.66	7.50	4.34	6.68	11.00
	1950	6.11	1.80	3.00	5.91	2.72	4.00	5.66	3.80	5.50	5.38	4.88	7.50	5.07	5.96	7.50	4.70	7.05	11.00

機型 Model	轉速 RPM	Type DCY-80 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-80	1000	5.01	1.63	2.20	4.53	2.61	3.00	4.01	3.59	5.50	3.40	4.57	5.50	2.73	5.55	7.50	1.96	6.52	7.50
	1100	5.61	1.79	3.00	5.13	2.87	4.00	4.61	3.95	5.50	4.01	5.02	7.50	3.34	6.10	7.50	2.56	7.18	11.00
	1200	6.21	1.96	3.00	5.73	3.13	4.00	5.21	4.31	5.50	4.61	5.48	7.50	3.94	6.65	11.00	3.16	7.83	11.00
	1300	6.81	2.12	3.00	6.33	3.39	4.00	5.81	4.66	5.50	5.21	5.94	7.50	4.54	7.21	11.00	3.76	8.48	11.00
	1400	7.41	2.28	3.00	6.93	3.65	5.50	6.41	5.02	7.50	5.81	6.39	7.50	5.14	7.76	11.00	4.37	9.13	11.00
	1500	8.01	2.45	3.00	7.53	3.91	5.50	7.01	5.38	7.50	6.41	6.85	11.00	5.74	8.32	11.00	4.97	9.79	15.00
	1600	8.61	2.61	3.00	8.13	4.18	5.50	7.61	5.74	7.50	7.01	7.31	11.00	6.34	8.87	11.00	5.57	10.44	15.00
	1650	8.91	2.69	4.00	8.43	4.31	5.50	7.91	5.92	7.50	7.31	7.54	11.00	6.64	9.15	11.00	5.87	10.76	15.00
	1750	9.51	2.85	4.00	9.04	4.57	5.50	8.51	6.28	7.50	7.91	7.99	11.00	7.24	9.70	15.00	6.47	11.42	15.00
	1850	10.11	3.02	4.00	9.64	4.83	7.50	9.11	6.64	11.00	8.51	8.45	11.00	7.84	10.26	15.00	7.07	12.07	15.00
1950	10.71	3.18	4.00	10.24	5.09	7.50	9.71	7.00	11.00	9.11	8.91	11.00	8.44	10.81	15.00	7.67	12.72	15.00	

機型 Model	轉速 RPM	Type DCY-100 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-100	1000	7.08	2.47	3.00	6.45	3.84	5.50	5.74	5.21	7.50	4.94	6.58	11.00	4.04	7.95	11.00	3.02	9.32	11.00
	1100	7.93	2.72	4.00	7.29	4.22	5.50	6.59	5.73	7.50	5.78	7.24	11.00	4.89	8.74	11.00	3.86	10.25	15.00
	1200	8.77	2.96	4.00	8.14	4.61	5.50	7.43	6.25	7.50	6.63	7.90	11.00	5.73	9.54	11.00	4.71	11.18	15.00
	1300	9.62	3.21	4.00	8.98	4.99	7.50	8.28	6.77	11.00	7.47	8.55	11.00	6.58	10.33	15.00	5.55	12.12	15.00
	1400	10.46	3.46	4.00	9.83	5.37	7.50	9.12	7.29	11.00	8.32	9.21	11.00	7.42	11.13	15.00	6.40	13.05	18.50
	1500	11.31	3.70	5.50	10.67	5.76	7.50	9.97	7.81	11.00	9.16	9.87	15.00	8.27	11.92	15.00	7.24	13.98	18.50
	1600	12.15	3.95	5.50	11.52	6.14	7.50	10.81	8.33	11.00	10.01	10.53	15.00	9.11	12.72	15.00	8.09	14.91	18.50
	1650	12.58	4.07	5.50	11.94	6.33	7.50	11.24	8.60	11.00	10.43	10.86	15.00	9.54	13.12	18.50	8.51	15.38	18.50
	1750	13.42	4.32	5.50	12.79	6.72	11.00	12.08	9.12	11.00	11.28	11.51	15.00	10.38	13.91	18.50	9.36	16.31	22.00
	1850	14.27	4.57	5.50	13.63	7.10	11.00	12.93	9.64	15.00	12.12	12.17	15.00	11.23	14.71	18.50	10.20	17.24	22.00
1950	15.11	4.81	5.50	14.48	7.49	11.00	13.77	10.16	15.00	12.97	12.83	15.00	12.07	15.50	18.50	11.05	18.17	22.00	

機型 Model	轉速 RPM	Type DCY-125A performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-125A	990	10.39	3.31	5.50	9.66	5.30	7.50	8.82	7.29	11.00	7.84	9.28	11.00	6.78	11.27	15.00	5.52	13.25	18.50
	1050	11.09	3.51	5.50	10.36	5.62	7.50	9.52	7.73	11.00	8.54	9.84	15.00	7.47	11.95	15.00	6.21	14.06	18.50
	1110	11.79	3.72	5.50	11.06	5.94	7.50	10.22	8.17	11.00	9.24	10.40	15.00	8.17	12.63	15.00	6.91	14.86	18.50
	1180	12.61	3.95	5.50	11.88	6.32	7.50	11.04	8.69	11.00	10.06	11.06	15.00	8.99	13.43	18.50	7.73	15.80	18.50
	1250	13.43	4.18	5.50	12.70	6.69	11.00	11.85	9.20	11.00	10.88	11.71	15.00	9.81	14.23	18.50	8.55	16.74	22.00
	1320	14.25	4.42	5.50	13.51	7.07	11.00	12.67	9.72	15.00	11.69	12.37	15.00	10.63	15.02	18.50	9.36	17.67	22.00
	1390	15.06	4.65	5.50	14.33	7.44	11.00	13.48	10.24	15.00	12.51	13.03	18.50	11.44	15.82	18.50	10.18	18.61	22.00
	1470	16.00	4.92	7.50	15.26	7.87	11.00	14.42	10.82	15.00	13.44	13.78	18.50	12.38	16.73	22.00	11.12	19.68	30.00
	1560	17.05	5.22	7.50	16.31	8.35	11.00	15.47	11.49	15.00	14.49	14.62	18.50	13.43	17.75	22.00	12.17	20.89	30.00
	1650	18.10	5.52	7.50	17.36	8.84	11.00	16.52	12.15	15.00	15.55	15.46	18.50	14.48	18.78	22.00	13.22	22.09	30.00
	1750	19.26	5.86	7.50	18.53	9.37	11.00	17.69	12.89	15.00	16.71	16.40	22.00	15.64	19.92	30.00	14.38	23.43	30.00
	1850	20.43	6.19	7.50	19.70	9.91	15.00	18.85	13.62	18.50	17.88	17.34	22.00	16.81	21.05	30.00	15.55	24.77	30.00

機型 Model	轉速 RPM	Type DCY-125 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-125	990	15.07	4.84	7.50	14.00	7.75	11.00	12.87	10.65	15.00	11.66	13.56	18.50	10.37	16.47	22.00	8.97	19.37	30.00
	1050	16.13	5.14	7.50	15.05	8.22	11.00	13.92	11.30	15.00	12.72	14.38	18.50	11.42	17.46	22.00	10.02	20.55	30.00
	1110	17.18	5.43	7.50	16.10	8.69	11.00	14.98	11.95	15.00	13.77	15.20	18.50	12.47	18.46	22.00	11.07	21.72	30.00
	1180	18.41	5.77	7.50	17.33	9.24	11.00	16.21	12.70	15.00	14.99	16.16	22.00	13.70	19.63	30.00	12.30	23.09	30.00
	1250	19.63	6.11	7.50	18.55	9.78	15.00	17.42	13.45	18.50	16.21	17.12	22.00	14.92	20.79	30.00	13.52	24.46	30.00
	1320	20.85	6.46	7.50	19.78	10.33	15.00	18.65	14.21	18.50	17.44	18.08	22.00	16.15	21.96	30.00	14.74	25.83	30.00
	1390	22.08	6.80	11.00	21.01	10.88	15.00	19.88	14.96	18.50	18.67	19.04	22.00	17.38	23.12	30.00	15.97	27.20	37.00
	1470	23.48	7.19	11.00	22.40	11.51	15.00	21.28	15.82	18.50	20.06	20.14	30.00	18.77	24.45	30.00	17.36	28.76	37.00
	1560	25.06	7.63	11.00	23.98	12.21	15.00	22.85	16.79	22.00	21.64	21.37	30.00	20.35	25.95	30.00	18.95	30.53	37.00
	1650	26.63	8.07	11.00	25.55	12.91	15.00	24.42	17.76	22.00	23.21	22.60	30.00	21.92	27.44	37.00	20.52	32.29	45.00
	1750	28.38	8.56	11.00	27.31	13.70	18.50	26.18	18.83	22.00	24.97	23.97	30.00	23.67	29.11	37.00	22.28	34.24	45.00
	1850	30.13	9.05	11.00	29.05	14.48	18.50	27.92	19.91	30.00	26.71	25.34	30.00	25.42	30.77	37.00	24.02	36.20	45.00

機型 Model	轉速 RPM	Type DCY-150 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-150	990	19.53	6.24	7.50	18.70	9.99	15.00	17.76	13.74	18.50	16.70	17.49	22.00	15.47	21.23	30.00	14.11	24.98	30.00
	1050	20.86	6.62	11.00	20.03	10.60	15.00	19.09	14.57	18.50	18.03	18.55	22.00	16.80	22.52	30.00	15.44	26.49	37.00
	1110	22.19	7.00	11.00	31.36	11.20	15.00	20.42	15.40	18.50	19.36	19.61	30.00	18.13	23.81	30.00	16.77	28.01	37.00
	1180	23.74	7.44	11.00	22.91	11.91	15.00	21.97	16.38	22.00	20.91	20.84	30.00	19.68	25.31	30.00	18.32	29.77	37.00
	1250	25.29	7.89	11.00	24.46	12.62	15.00	23.52	17.35	22.00	22.46	22.08	30.00	21.23	26.81	37.00	19.87	31.54	37.00
	1320	26.84	8.33	11.00	26.01	13.32	18.50	25.07	18.32	22.00	24.00	23.31	30.00	22.78	28.31	37.00	21.41	33.31	45.00
	1390	28.39	8.77	11.00	27.56	14.03	18.50	26.62	19.29	30.00	25.55	24.55	30.00	24.33	29.81	37.00	22.96	35.07	45.00
	1470	30.16	9.27	11.00	29.33	14.84	18.50	28.39	20.40	30.00	27.32	25.96	30.00	26.10	31.53	37.00	24.73	37.09	45.00
	1560	32.15	9.84	15.00	31.32	15.74	18.50	30.38	21.65	30.00	29.31	27.55	37.00	28.09	33.46	45.00	26.72	39.36	55.00
	1650	34.14	10.41	15.00	33.31	16.65	22.00	32.37	22.90	30.00	31.30	29.14	37.00	30.08	35.39	45.00	28.71	41.63	55.00
	1750	36.35	11.04	15.00	35.52	17.66	22.00	34.58	24.29	30.00	33.51	30.91	37.00	32.29	37.53	45.00	30.92	44.16	55.00
	1850	38.56	11.67	15.00	37.73	18.67	22.00	36.78	25.67	30.00	35.71	32.68	45.00	34.50	39.68	55.00	33.12	46.68	55.00

機型 Model	轉速 RPM	Type DCY-200A performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-200A	990	32.00	10.02	18.50	30.86	16.03	18.50	29.65	22.04	30.00	28.31	28.05	37.00	26.89	34.06	45.00	25.31	40.07	55.00
	1050	34.29	10.62	18.50	33.15	17.00	18.50	31.94	23.37	30.00	30.60	29.75	37.00	29.18	36.12	45.00	27.60	42.50	55.00
	1110	36.58	11.23	18.50	35.43	17.97	22.00	34.22	24.71	30.00	32.88	31.45	37.00	31.46	38.19	45.00	29.87	44.92	55.00
	1180	39.25	11.94	18.50	38.10	19.10	30.00	36.89	26.27	37.00	35.55	33.43	45.00	34.13	40.59	55.00	32.54	47.76	75.00
	1250	41.93	12.65	18.50	40.78	20.24	30.00	39.57	27.82	37.00	38.23	35.41	45.00	36.81	43.00	55.00	35.22	50.59	75.00
	1320	44.60	13.36	18.50	43.45	21.37	30.00	42.24	29.38	37.00	40.90	37.40	45.00	39.48	45.41	55.00	37.89	53.42	75.00
	1390	47.27	14.06	18.50	46.12	22.50	30.00	44.91	30.94	37.00	43.57	39.38	55.00	42.15	47.82	75.00	40.56	56.26	75.00
	1470	50.32	14.87	18.50	49.17	23.80	30.00	47.96	32.72	45.00	46.62	41.65	55.00	45.20	50.57	75.00	43.61	59.49	75.00

機型 Model	轉速 RPM	Type DCY-200 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-200	990	41.57	12.88	15.00	40.07	20.61	30.00	38.48	28.33	37.00	36.73	36.06	45.00	34.89	43.79	55.00	32.84	51.52	75.00
	1050	44.50	13.66	18.50	43.00	21.86	30.00	41.41	30.05	37.00	39.67	38.25	45.00	37.82	46.44	55.00	35.78	54.64	75.00
	1110	47.42	14.44	18.50	45.91	23.10	30.00	44.33	31.77	37.00	42.58	40.43	55.00	40.74	49.10	75.00	38.68	57.76	75.00
	1180	50.82	15.35	18.50	49.32	24.56	30.00	47.73	33.77	45.00	45.99	42.98	55.00	44.14	52.19	75.00	42.09	61.40	75.00
	1250	54.23	16.26	22.00	52.72	26.02	30.00	51.14	35.77	45.00	49.40	45.53	55.00	47.55	55.29	75.00	45.50	65.05	75.00
	1320	57.62	17.17	22.00	56.11	27.48	37.00	54.53	37.78	45.00	52.79	48.08	75.00	50.95	58.38	75.00	48.90	68.69	90.00
	1390	61.00	18.08	22.00	59.49	28.93	37.00	57.91	39.78	55.00	56.17	50.63	75.00	54.33	61.48	75.00	52.28	72.33	90.00
	1470	64.84	19.12	30.00	63.34	30.60	37.00	61.77	42.07	55.00	60.02	53.55	75.00	58.18	65.02	75.00	56.14	76.49	90.00

機型 Model	轉速 RPM	Type DCY-250 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-250	990	57.43	17.17	22	55.39	27.48	37	53.22	37.78	45	50.82	48.08	75	48.30	58.38	75	45.49	68.69	95
	1050	61.44	18.21	22	59.40	29.14	37	57.23	40.07	55	54.84	51.00	75	52.31	61.92	75	49.52	72.85	95
	1110	65.43	19.25	30	63.37	30.81	37	61.22	42.36	55	58.82	53.91	75	56.30	65.46	90	53.48	77.01	95
	1180	70.07	20.47	30	68.03	32.75	45	65.86	45.03	55	63.48	57.31	75	60.95	69.59	90	58.15	81.87	95
	1250	74.72	21.68	30	72.67	34.69	45	70.52	47.70	55	68.14	60.71	75	65.61	73.72	90	62.80	86.73	110
	1320	79.34	22.90	30	77.29	36.63	45	75.14	50.37	75	72.76	64.11	75	70.24	77.85	90	67.44	91.58	110
	1390	83.94	24.11	30	81.89	38.58	45	79.74	53.04	75	77.36	67.51	90	74.84	81.97	110	72.04	96.44	132
	1470	89.16	25.50	30	87.13	40.80	55	84.99	56.10	75	82.60	71.39	90	80.09	86.69	110	77.30	101.99	132

機型 Model	轉速 RPM	Type DCY-300A performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-300A	990	77.99	22.90	30	75.23	36.63	45	72.30	50.37	75	69.22	64.11	75	65.77	77.85	90	61.91	91.58	110
	1050	82.39	24.28	30	80.64	38.85	45	77.68	53.42	75	74.61	67.99	90	71.15	82.56	110	67.30	97.13	132
	1110	88.76	25.67	30	85.98	41.07	55	83.05	56.48	75	79.95	71.88	90	76.49	87.28	110	72.65	102.68	132
	1180	95.00	27.29	37	92.24	43.66	55	89.27	60.04	75	86.15	76.41	90	82.69	92.79	110	78.84	109.16	132
	1250	101.24	28.91	37	98.47	46.25	55	95.47	63.60	75	92.35	80.95	110	88.89	98.29	132	85.04	115.64	160
	1320	107.43	30.53	37	104.66	48.84	75	101.67	67.16	90	98.55	85.48	110	95.09	103.79	132	91.24	122.11	160
	1390	113.58	32.15	45	110.82	51.43	75	107.86	70.72	90	104.70	90.01	110	101.28	109.30	132	97.43	128.59	160
	1470	120.56	34.00	45	117.83	54.40	75	114.85	74.79	90	111.65	95.19	110	108.20	115.59	160	104.36	135.99	160

機型 Model	轉速 RPM	Type DCY-300 performakwce																	
		-1000mmAq			-2000mmAq			-3000mmAq			-4000mmAq			-5000mmAq			-6000mmAq		
		Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw	Qs	La	kw
DCY-300	800	98.94	29.11	40	95.93	46.58	55	92.85	64.05	75	89.21	81.52	110	85.17	98.99	132	80.67	116.46	160
	900	112.33	32.75	40	109.32	52.40	75	106.24	72.06	90	102.60	91.71	110	98.56	111.36	132	94.06	131.01	160
	1000	125.72	36.39	55	122.71	58.23	75	119.63	80.06	110	115.99	101.90	132	111.95	123.73	160	107.45	145.57	200
	1100	139.05	40.03	55	136.10	64.05	75	133.02	88.07	110	129.38	112.09	132	125.34	136.11	160	120.84	160.13	200
	1200	152.44	43.67	55	149.49	69.87	90	146.41	96.08	132	142.76	122.28	160	138.73	148.48	200	134.23	174.68	250
	1300	165.82	47.31	55	162.88	75.70	90	159.80	104.08	132	156.15	132.47	160	152.12	160.85	200	147.62	189.24	250
	1400	179.20	50.95	75	176.27	81.52	110	173.19	112.09	132	169.54	142.66	200	165.51	173.23	200	161.01	203.80	250

審核：钱芳（代）2015/10/15

24小时服务热线：177 1516 6720

网址：www.ks-dcy.com